

30"

HIGH VELOCITY FAN



STANDARD YM - YOKE MOUNT

ADDITIONAL MOUNTING OPTIONS:



RM Rack Mount

135 lbs



CW Column-Wall

145 lbs



PS Portable Stroller

161 lbs



PB Pedestal Base

140 lbs

SHIPPING WEIGHTS:

SIZE	CFM	HP	FAN DIMENSIONS			AIR THROW DISTANCE	SHIPPING WEIGHT
			W	D	ID		
30"	12,000	1	37"	22"	30.875"	200'	125 lbs

FEATURES

Propeller: 30" Diameter, 2 Blade GalvAlum, 15°
Fan Inlet/Outlet: 14 Gauge Spun Steel
Finger Guards: OSHA Compliant, Spiral Wound Steel
Power Cord (115V Only): 12' Length (Switch Optional)
RPM: 1800*/1200
Decibels: 82.2 @ 20' - 85.5 @ 3' (1800)
Coverage: 12,000 ft²

Warranty: 2 Years

MOTOR

VOLTAGE	MOTOR AMPS	RUNNING AMPS
115V/208-230V	13.4/6.8-6.7	12.9/6.6-6.5
208-230/460V*	3.6-3.5/1.8	3.4-3.3/1.7
277V	5.6	5.4


Enclosure: TEAO Standard

Frame: 56

Ambient Temperature: 104°F

Duty Cycle: Continuous

*standard



AIR FLOW PATTERN